

#### SUZUKI MOTOR CORPORATION

**EXECUTIVE ORDER A-259-0100** 

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

#### IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP			HAUST EMISSION NDARD CATEGORY		USEFUL LIFE (miles)			MEDIATE USE LIANCE full in-use; h. / evap. late in-use)	FUEL TYPE	
2007	7SKXT2,745E1	LDT: <6000# GVW, 3751-5750#		EV II" Low Emission ehicle (LEV II LEV)	EXH / ORVR	EVAP	E	(H	EVAP	Gasoline	
		LVW	(		150K	150K	<u> </u>	* *			
No.	ECS & SPECIAL FEATURES			EVAPORATIVE FAMILY (EVAF) DI:						MENT (L)	
1	2WU-TWC,TWC, 2AFS,2HO2S, SFI, EGR, OBD(F)			7SKXR	7 K						
*	*			*					_	_	
*	*			*				2.	,		
•	*			*							

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

### **BE IT FURTHER RESOLVED:**

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

#### **BE IT FURTHER RESOLVED:**

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

#### BE IT FURTHER RESOLVED:

Additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of June 2006.

Allen Lyons, Chief &

Mobile Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

# **ATTACHMENT**

### **EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS**

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/ml]						CH4=methane; NMOG=non-CH4 organic gas: NMHC=non-CH4 hydrocarbon; CÖ=carbon monoxide; NOx=oxides of nitrogen; IHCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal+ hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram										
CERT	STD	NMOG	NMHC	NMHC	mi=mile: K=	nile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure										
		CERT	[g/mi]	00 (/1)		NÖx [g/mi]		HCHO [mg/mi]		PM [g/ml]		Hwy NOx [g/ml]				
0.051	0.065	[g/mi]	[g/mi]	[9/1111]	CERT	STD	CERT	STD	CERT	STD	CERT	redure	STD			
District Color	@ 50K	0.027	•	0.075	0.3	3.4	0.02	0.05	0.1	15.	*	*	0.01	0.07		
	@ UL	0.044	•	0.090	0.8	4.2	0.04	0.07	0.2	18.	•	*	0.04	0.09		
<b>.</b> 0	50°F & 4K	0.078	*	0.150	0.7	3.4	0.01	0.05	0.4	30.	*	*	*	*		

C	CO [g/ml]		encilly and Suggested by	NMHC+N (comp		CO [			+NOx [US06]	co [	g/mi] 06]		+NOx [SC03]	00 [sc	
	0°F & 50K	200		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	1.B	7	SFTP @ 4000 miles	*	*	*	*	0.05	0.25	2.0	10.5	0.01	0.27	0.2	3.5
STD	12.5		SFTP @ * miles	•	*	*	*	*	*	*	*	*	*	*	*

Evaporative Family	3-Days Diurna (grams/te		2-Days Diurn (grams/te		Runnin (grams/m		On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
,	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
7SKXR0120466	0.27	0.65	0.53	0.85	0.0004	0.05	0.02	0.20	
*	•	*	*	*	•	*	*	*	
*	*	*	*	•	*	*	*	*	
•	-	*	*	*	•	*	*	*	
	<u> </u>			<u> </u>			<u> </u>		

<sup>\* =</sup> not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; HO2S=heated O2S; AFS/HAFS=air-fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

# 2007 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN-I COMPI (*=N/A or: A/E=exi	IEDIATE USE LIANCE full In-use; n. / evap. ate in-use)	PHASE-IN STD.	OBD II
					EXH	EVAP		
SUZUKI	GRAND VITARA	7SKXR0120466	1	2.7	*	*	SFTP	Full
SUZUKI	GRAND VITARA AWD	7SKXR0120466	1	2.7	*	*	SFTP	Full